CUBE PRO [Y1 AGM]

CUBE PRO is not just a new lighting tower, but the real and only "ALL IN ONE" product! It embodies all the innovations and new technologies that Generac Mobile[®] has developed in over 20 years at the top of the industry as manufacturer. We have brought together all the Rental needs, in one single product.



Engine note: both EU Stage V and unregulated version available.





GENERAC[®] G4 LED High efficiency LED floodlights designed by Generac Mobile[®]. Special version with adjustable light power output.

ALL IN ONE

PRO is the only lighting tower technology to offer altogether:

 the *future*, with 100% battery-powered supply;
the *present*, with the latest generation hybrid power supply;
the *tradition*, with low consumption diesel engine.

All in one model.

| | COBE PRO TLAGM | | | | |
|---|--------------------------|-----------------------|---------|---------|---------|
| TECHNICAL DATA | | | | | |
| Min. dimensions (mm) | Length x Width x Height | 1230 x 1160 x 2300 | | | |
| Max. dimensions (mm) | Length x Width x Height | 1790 x 1735 x 8100 | | | |
| Dry weight (kg) | | 1175 | | | |
| Engine model | | Yanmar L70V5 Stage V | | | |
| Avg. sound pressure | dB(A) @ 7m | 0 - 68 | | | |
| Battery type | | AGM | | | |
| Dimmer switch | Light intensity | 25% | 50% | 75% | 100% |
| Max. lamps power (W) | | 4 x 60 | 4 x 120 | 4 x 180 | 4 x 240 |
| Lamps type | | G4 LED | G4 LED | G4 LED | G4 LED |
| Max. total lumen (Lm) | | 41040 | 76184 | 107668 | 139200 |
| Max. illuminated area (m ²) | | 1500 | 2200 | 2700 | 3100 |
| Battery recharging time (h) | | 6:11 | 5:18 | 5:09 | 4:29 |
| Running time - Battery mode (h) | | 19:46 | 10:07 | 5:11 | 3:45 |
| Running time - Generator mode (h) | | 241 | 227 | 208 | 194 |
| Running time - Hybrid mode (h) | | 707 | 439 | 285 | 247 |
| Mast lifting system | M: Manual / H: Hydraulic | Н | | | |
| Mast rotation (°) | | 340 | | | |
| Wind speed resistance (km/h) | | 110 | | | |
| Alternator | kVA/V/Hz | 5/230/50 - 5/240/60 | | | |
| CEE inlet plug (external power) | A/V/Hz | 16/230/50 - 16/240/60 | | | |
| Multipin inlet plug (solar kit) | √: Yes / ●: No | \checkmark | | | |
| Tank capacity (liters) | | 160 (150 net) | | | |
| Liquid containment tank (110%) | √: Yes / ●: No | \checkmark | | | |

CUBE PRO Y1 AGM