

DF 3000 MPT

EN_CTS_DF-3000-MPT_20-11_r2.0



Standard version on base



Version on optional road trailer

STANDARD EQUIPMENT

- Telescopic vertical mast (max. height: 4m)
- 1000 litres plastic water tank
- 3.7 kW - 230 V integrated generating set
- Integrated control panel
- Stainless steel crown with nozzles
- Nebulizer cone foldable for shipment
- Telescopic mast with double crank winch
- Water Supply and Main Electricity network connections
- High pressure washer connection
- Water drain system
- Installed on base with forklift pockets

OPTIONS

- Low speed trailer (without brakes)
- Road trailer type A (straight)
- Road trailer type CM (adjustable)
- Documents for road registration (EU)

DF 3000 MPT

TECHNICAL DATA

Electrical engine power (kW)		2.2
Integrated generating set		Diesel engine - 3.7 kW - 230 V - 3000 RPM - 50 Hz ¹
Max. horizontal range (m)	Without wind	20
Max. covered area (m ²)	With rotation	1170
Running time (min)		160
Fuel tank capacity (L)		18
Water tank capacity (L)		1000
Water consumption (L/min)		6.25
Water inlet filter (µm)		170
Rotation angle (°)		335
Tilting angle (°)	Min. / Max.	-30 / +10
Dimensions on base (mm)	L x W x H (min./max.)	2374 x 1210 x 2230/3920
Dimensions on road trailer ² (mm)	L x W x H (min./max.)	3920 x 2015 x 2780/4470
Dry weight on base (mm)		490
Dry weight on road trailer ² (kg)		840

¹Also available in 60 Hz version - ²Measures referred to optional road trailer type A