

DF 7500 - DF 15000 - DF 20000

EN_CTS_DF-7500-15000-20000_20-11_r2.0



STANDARD EQUIPMENT

- Integrated control panel
- Phase inverter
- Pump with peripheral impeller
- Flowmeter for pump protection
- Pressure gauge for outlet pressure reading
- Stainless steel crown with nozzles
- Water drain system
- Equipped with two wheels, tow bar and forklift pockets
- Two height adjustable stabilizers

OPTIONS

- Remote control
- Road trailer type CM (adjustable)
- Documents for road registration (EU)
- Automatic rotation
- Electric tilting
- Dosing pump for chemical additives
- Water supply pump
- Arctic kit
- Side forklift pockets (for low speed trailer only)
- Dedicated colour (RAL) (for spray cannon only)
- Ball or eyelet hitch

		DF 7500	DF 15000	DF 20000
TECHNICAL DATA				
Electrical engine power (kW)		7.5	15	20
Smallest generator required		Three-phase - 20 kW	Three-phase - 35 kW	Three-phase - 50 kW
Max. horizontal range (m)	Without wind	30 - 40	40 - 50	50 - 60
Max. vertical range (m)	Without wind	16	20	24
Max. covered area (m ²)	With rotation on	4800	7190	10355
Electrical connection	Inlet plug	Three-phase - 32 A	Three-phase - 32 A	Three-phase - 63 A
Water connection	Available plugs	UNI 45 / STORZ / CAMLOCK	UNI 45 / STORZ / CAMLOCK	UNI 45 / STORZ / CAMLOCK
Min. inlet pressure (bar)		1	1	1
Water consumption (L/min)		52	60	70
Water inlet filter (µm)		180	180	180
Rotation angle (°)		335	335	335
Tilting angle (°)	Min. / Max.	+0° / +40°	+0° / +40°	+0° / +40°
Dimensions (mm)	Length x Width x Height	3300 x 1830 x 2180	3300 x 1830 x 2180	3300 x 1830 x 2180
Weight (kg)		717	767	807